



HPS 21 SERIES

Processed Active Speaker 15"

SPECIFICATIONS	
Frequency response	45-18KHZ
Coverage	H100° x V60°
Continuous	75W
Music	150W
Peak	300W
Sensitivity 1w/1m	95dB
Peak spl	120dB
System impedance	4 OHM
Crossover section	2 way
Cross over frequency	3500HZ
Input Connector	XL,RCA,6,35TRS
Dimension (hwxwd)	485x445x745cm

Equipped with 300-watt power with Digital amplifier (SMTP) ,high-quality transducers,and modern DSs,For every unit with sound system delivers the kind of stellar audio performance that sets the stage for success.And that makes it the perfect companion for the discerning performer.



Model	HPS2108/A	HPS2110/A	HPS2112/A	HPS2115/A
System type	2-way Model speaker box	2-way Model speaker box	2-way Model speaker box	2-way Model speaker box
Woofers	8" woofer,30oz,38mm vc,4ohm/8ohm	10" woofer,40oz,50mm vc,4ohm/8ohm	12" woofer,50oz,65mm vc,4ohm/8ohm	15" woofer,60oz,75mm vc,4ohm/8ohm
Tweeter	25mm TiDiap.driver,10OZ,8ohm	25mm TiDiap.driver,10OZ,8ohm	34mm TiDiap.driver,14OZ,8ohm	44mm TiDiap.driver,23OZ,8ohm