



HPS 36 SERIES

Processed Active Speaker 15"

SPECIFICATIONS	
Frequency response	45-18K-HZ
Coverage	H90° x V40°
Continuous	250W
Music	500W
Peak	1000W
Sensitivity 1w/1m	98dB
Peak spl	128dB
System impedance	4 OHM
Crossover section	2 way
Cross over frequency	3500HZ
Input Connector	RCA,XLR,6.35TRS
Dimension (h x w x d)	515X465X755CM

With amazing feature and the ultra compact pack power amplifier, based on the successful digital amplifier technology for maximum efficiency.



Model	HPS3608/A	HPS3610/A	HPS3612/A	HPS3615/A
System type	2-way Model speaker box	2-way Model speaker box	2-way Model speaker box	2-way Model speaker box
Woofers	8" woofer, 30oz, 38mm vc, 4ohm/8ohm	10" woofer, 40oz, 50mm vc, 4ohm/8ohm	12" woofer, 50oz, 65mm vc, 4ohm/8ohm	15" woofer, 60oz, 75mm vc, 4ohm/8ohm
Tweeter	25mm TiDiap.driver, 100Z, 8ohm	25mm TiDiap.driver, 100Z, 8ohm	34mm TiDiap.driver, 140Z, 8ohm	44mm TiDiap.driver, 230Z, 8ohm