



HPS 39 SERIES

Processed Active Speaker 15 "

SPECIFICATIONS	
Frequency response	45-20K hz
Coverage	H90° /70° x V60°
Continuous	120 w
Music	240 w
Peak	480 w
Sensitivity 1w/1m	98db
Peak spl	125db
System impedance	4 ohm
Crossover section	2 way
Cross over frequency	2.0K hz , 2.0K hz
Input Connector	RCA,6.35TRS,XLR,Speakon
Dimension (hwxwd)	99.0×45.5×76.0cm(2pcs)

The unit speaker is not only the line, it is also the reference standard for the entire class.

Model	HPS3908/A	HPS3910/A	HPS3912/A	HPS3915/A
System type	2-way Model speaker box	2-way Model speaker box	2-way Model speaker box	2-way Model speaker box
Woofer	8 " woofer,30oz,38mm vc,4ohm/8ohm	10 " woofer,40oz,50mm vc,4ohm/8ohm	12 " woofer,50oz,65mm vc,4ohm/8ohm	15 " woofer,60oz,75mm vc,4ohm/8ohm
Tweeter	25mm TiDiap.driver,10OZ,8ohm	25mm TiDiap.driver,10OZ,8ohm	34mm TiDiap.driver,14OZ,8ohm	44mm TiDiap.driver,23OZ,8ohm