



HPS 01 SERIES

Processed Active Speaker 15"

SPECIFICATIONS	
Frequency response	50-20K-HZ
Coverage	H90° × V60°
Continuous	400W
Music	800W
Peak	1600W
Sensitivity 1w/1m	94dB
Peak spl	126dB
System impedance	4 ohm
Crossover section	2 way
Cross over frequency	2500HZ
Input Connector	XLR,RCA,6.3STRS
Dimension (lwxwxh)	510×505×75.5cm

The speaker offers powered loudspeaker with modern AB Analog Amplifier technology, without having to miss out on professional features and outstanding audio performance.



Model	HPS0108/A	HPS0110/A	HPS0112/A	HPS0115/A
System type	2-way Model speaker box	2-way Model speaker box	2-way Model speaker box	2-way Model speaker box
Woofers	8" woofer, 30oz, 38mm vc, 4ohm/8ohm	10" woofer, 40oz, 50mm vc, 4ohm/8ohm	12" woofer, 50oz, 65mm vc, 4ohm/8ohm	15" woofer, 60oz, 75mm vc, 4ohm/8ohm
Tweeter	25mm TiDiap.driver, 100Z, 8ohm	25mm TiDiap.driver, 100Z, 8ohm	34mm TiDiap.driver, 140Z, 8ohm	44mm TiDiap.driver, 230Z, 8ohm