



**HPS 02 SERIES**  
Processed Active Speaker 15 "

SPECIFICATIONS	
Frequency response	55-20K hz
Coverage	H90° x V30° XvV45°
Continuous	25 w
Music	50w
Peak	100 w
Sensitivity 1w/1m	91db
Peak spl	111db
System impedance	4 ohm
Crossover section	2 way
Cross over frequency	5000HZ
Input Connector	RCA,6.35TRS
Dimension (hwxwd)	385×325×53.0cm

With amazing feature and ultra compact pack power amplifier, based on the successful digital amplifier technology for maximum efficiency.



Model	HPS0208/A	HPS0210/A	HPS0212/A	HPS0215/A
System type	2-way Model speaker box	2-way Model speaker box	2-way Model speaker box	2-way Model speaker box
Woofer	8 " woofer,30oz,38mm vc,4ohm/8ohm	10 " woofer,40oz,50mm vc,4ohm/8ohm	12 " woofer,50oz,65mm vc,4ohm/8ohm	15 " woofer,60oz,75mm vc,4ohm/8ohm
Tweeter	25mm TiDiap.driver,10OZ,8ohm	25mm TiDiap.driver,10OZ,8ohm	34mm TiDiap.driver,14OZ,8ohm	44mm TiDiap.driver,23OZ,8ohm