



### HPS 34 SERIES

Processed Active Speaker 15 "

SPECIFICATIONS	
Frequency response	45-18K-HZ
Coverage	H90° × V60°
Continuous	180W
Music	360W
Peak	720W
Sensitivity 1w/1m	96dB
Peak spl	125dB
System impedance	8 OHM
Crossover section	2 way
Cross over frequency	2500HZ
Input Connector	XL,R,CA,Speakon
Dimension (h×w×d)	495 × 405 × 75.0cm

A powerful dynamic design for aggressive clean-cut lines.

A sturdy light-weight enclosure that ensures great versatility and is ready for installation. Thanks to its special mounting points and optional accessories.



Model	HPS3408/A	HPS3410/A	HPS3412/A	HPS3415/A
System type	2-way Model speaker box	2-way Model speaker box	2-way Model speaker box	2-way Model speaker box
Woofer	8 " woofer,30oz,38mm vc,4ohm/8ohm	10 " woofer,40oz,50mm vc,4ohm/8ohm	12 " woofer,50oz,65mm vc,4ohm/8ohm	15 " woofer,60oz,75mm vc,4ohm/8ohm
Tweeter	25mm Ti,Diap.driver,10OZ,8ohm	25mm Ti,Diap.driver,10OZ,8ohm	34mm Ti,Diap.driver,14OZ,8ohm	44mm Ti,Diap.driver,23OZ,8ohm